



SMARTSENS

CMOS图像传感器

CMOS IMAGE SENSOR

SC235HGS 产品单页

SC235HGS Product Flyer

- 搭载全新SmartGS®-2 Plus技术的BSI架构全局快门面阵CMOS图像传感器

BSI global shutter CMOS image sensor with SmartGS®-2 Plus technology

- 集高影像性能、高速、高动态范围三大性能优势于一身
Achieves high imaging performance, high speed, and high dynamic range

公司简介 | Company Profile

思特威(上海)电子科技股份有限公司 SmartSens Technology (股票简称:思特威,股票代码:688213)是一家从事CMOS图像传感器芯片产品研发、设计和销售的高新技术企业,总部设立于中国上海,在多个城市及国家设有研发中心。

自成立以来,思特威始终专注于高端成像技术的创新与研发,凭借自身性能优势得到了众多客户的认可和青睐。作为致力于提供多场景应用、全性能覆盖的CMOS图像传感器产品企业,公司产品已覆盖了安防监控、机器视觉、智能车载电子、智能手机等多场景应用领域的全性能需求。

思特威将秉持“以前沿智能成像技术,让人们更好地看到和认知世界”的愿景,以客户需求为核心动力,持续推动前沿成像技术升级,拓展产品应用领域,与合作伙伴一起助推未来智能影像技术的深化发展。

SmartSens Technology (Shanghai) Co., Ltd. (Stock Code: 688213) is a high-performance CMOS image sensor (CIS) chip design company. It is headquartered in Shanghai and has research centers in many cities around the world.

SmartSens has been dedicated to pushing forward the frontier of imaging technology and growing in popularity among customers since it was established. SmartSens' CMOS image sensors provide advanced imaging solutions for a broad range of areas such as surveillance, machine vision, automotive and cellphone cameras.

SmartSens is committed to continuous innovation of products and fueling growth in numerous industries by delivering a more comprehensive portfolio of image sensors.

SC235HGS Product Flyer

SmartGS[®]-2 Plus Series



项目 Item	参数 Parameters
Resolution	2MP
Pixel Array	1616 (H) × 1216 (V)
Pixel Size	3.45μm × 3.45μm
Optical Format	1/2.6"
Max Frame Rate	1600 × 1200 @ 130 fps 10-bit MIPI/LVDS 4 Lane @ 1.5V
	1600 × 1200 @ 100 fps 10-bit MIPI/LVDS 2 Lane @ 1.2V
	1440 × 1080 @ 150 fps 10-bit MIPI/LVDS 4 Lane @ 1.5V
	1440 × 1080 @ 120 fps 10-bit MIPI/LVDS 2 Lane @ 1.5V
	1280 × 1024 @ 160 fps 10-bit MIPI/LVDS 4 Lane @ 1.5V
	1280 × 1024 @ 120 fps 10-bit MIPI/LVDS 2 Lane @ 1.5V
	640 × 480 @ 300 fps 10-bit MIPI/LVDS 1 Lane @ 1.2V
	12/10/8-bit 1/2/4 Lane MIPI
	12/10/8-bit 1/2/4 Lane LVDS
	10-bit DVP parallel
Output Interface	
Output Format	10-bit RAW
CRA	0°
Sensitivity	13490 mV/lux·s
Dynamic Range	Linear Mode: 61.5dB
	HDR Mode: >90dB
SNR	37.5 dB
Operation Temperature	-30°C ~ +85°C
Best IQ Temperature	-20°C ~ +60°C
Power Supply	AVDD = 3.0/2.8±0.1V
	DVDD = 1.2/1.5±0.06V
Package Size	6.48mm × 5.18mm
	48-pin, CSP;CLGA

产品特性 | Features

- 高帧率面阵CMOS图像传感器
High frame rate CMOS image sensor
- 先进SmartGS[®]-2 Plus技术加持
广泛适用于工业检测场景
Incorporating advanced technologies including SmartGS[®]-2 Plus, the sensor is ideal for industrial inspection
- HDR功能提升工业检测精度
The HDR function leads to higher precision of industrial inspection

应用场景 | Applications

- 工业相机
Industrial Machine Vision Cameras



WeChat



LinkedIn

Website	www.smartsensotech.com
安防监控类应用	security@smartsensotech.com
车载电子类应用	automotive@smartsensotech.com
工业及机器视觉	machinevision@smartsensotech.com
智能手机类应用	mobile_cs@smartsensotech.com
其他	cs@smartsensotech.com

- 上海办公室
上海市闵行区田林路889号科技绿洲四期8号楼
Building 8, Shanghai Business Park IV, No. 889 Tianlin Road,
Minhang District, Shanghai
Tel: 021-6485-3570
- 深圳办公室
深圳市龙岗区坂田街道雅宝路1号 星河WORLD B座2801室
B2801, Building B, Galaxy WORLD, No.1 Yabao Road,
Bantian Street, Longgang District, Shenzhen
Tel: 0755-2373-9713

- 北京办公室
北京市经济技术开发区荣华南路2号大族广场T6座2201室
Room 2201, Building T6, Dazhu Plaza, No.2, South Ronghua
Road, Economic-Technological Development Area, Beijing
Tel: 010-6786-3626
- 香港办公室
香港观塘鸿图道21号讯科中心10楼F室
RM F, 10/F, INFOTECH CENTRE, 21 HUNG TO RD
- 美国(圣何塞)
加利福尼亚州圣何塞市史蒂文森克里克大道4340号280室
4340 Stevens Creek Blvd, Suite 280, San Jose CA95129
Tel: +1 408 981 6626